WHITE LIGHT STRIPS

# 180lm/W 120LED/M 10mm LED strip

**TRU-SWB12V10MM120LEDM**

180lm/W 120LED/M 10mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



## Product specifications

| | |
|---|---|
| Truled part number | TRU-SWB12V10MM120LEDM |
| Category | LED strips |
| Product type | White light strips |

## Configuration reference

### TRU-SWB12V10MM120LEDM-A

| | |
|---|---|
| Dimension | L3000*W10*H1mm [L118*W0.4*H0.04in.] |
| Increment | 33.33mm [1.3in] |
| LED Type | SMD2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | 12VDC |
| Power | 10W/M [3.05W/ft.] |
| CCT / Wavelength | 2700K 3000K 3500K 4000K 5000K 6500K |
| Brightness @4000K&CRI80 | 1600lm/M [490lm/ft.] |
| Light Efficiency @4000K&CRI80 | 160lm/W |
| Brightness @4000K&CRI90 | Not specified |
| Light Efficiency @4000K&CRI90 | Not specified |
| Beam Angle | 120° |
| IP Rating | IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet] |

## Configuration reference

### TRU-SWB12V10MM120LEDM-B

| | |
|---|---|
| Dimension | L3000*W10*H1mm [L118*W0.4*H0.04in.] |
| Increment | 33.33mm [1.3in] |
| LED Type | SMD2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | 12VDC |
| Power | 10W/M [3.05W/ft.] |
| CCT / Wavelength | 2700K 3000K 3500K 4000K 5000K 6500K |
| Brightness @4000K&CRI80 | 1800lm/M [550lm/ft.] |
| Light Efficiency @4000K&CRI80 | 180lm/W |
| Brightness @4000K&CRI90 | Not specified |
| Light Efficiency @4000K&CRI90 | Not specified |
| Beam Angle | 120° |
| IP Rating | IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet] |

## Configuration reference

### TRU-SWB12V10MM120LEDM-C

| | |
|---|---|
| Dimension | L3000*W10*H1mm [L118*W0.4*H0.04in.] |
| Increment | 33.33mm [1.3in] |
| LED Type | SMD2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | 12VDC |
| Power | 12W/M [3.66W/ft.] |
| CCT / Wavelength | 2700K 3000K 3500K 4000K 5000K 6500K |
| Brightness @4000K&CRI80 | Not specified |
| Light Efficiency @4000K&CRI80 | Not specified |
| Brightness @4000K&CRI90 | 1600lm/M [490lm/ft.] |
| Light Efficiency @4000K&CRI90 | 136lm/W |
| Beam Angle | 120° |
| IP Rating | IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet] |

## Configuration reference

### TRU-SWB12V10MM120LEDM-D

| | |
|---|---|
| Dimension | L3000*W10*H1mm [L118*W0.4*H0.04in.] |
| Increment | 33.33mm [1.3in] |
| LED Type | SMD2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | 12VDC |
| Power | 12W/M [3.66W/ft.] |
| CCT / Wavelength | 2700K 3000K 3500K 4000K 5000K 6500K |
| Brightness @4000K&CRI80 | Not specified |
| Light Efficiency @4000K&CRI80 | Not specified |
| Brightness @4000K&CRI90 | 1800lm/M [550lm/ft.] |
| Light Efficiency @4000K&CRI90 | 153lm/W |
| Beam Angle | 120° |
| IP Rating | IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet] |

## Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.