WHITE LIGHT STRIPS

High-Efficacy Ultra-Long 173lm/W 20M 24V 128LED/M LED strip

TRU-SWB24V128LEDM

High-Efficacy Ultra-Long 173lm/W 20M 24V 128LED/M LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SWB24V128LEDM
Category	LED strips
Product type	White light strips

Configuration reference

TRU-SWB24V128LEDM-A

Dimension	L20000*W8*H1.75mm [L787*W0.31*H0.07in.]
Increment	62.5mm [2.46in.]
LED Type	SMD2835
LED Qty	128LED/M [39LED/ft.]
Voltage	24VDC
Power	3W/M [0.91W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	480lm/M [146lm/ft.]
Light Efficiency @4000K&CRI90	160m/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus [Dry/Damp/Wet]

Configuration reference

TRU-SWB24V128LEDM-B

Dimension	L14000*W8*H1.75mm [L551*W0.31*H0.07in.]
Increment	62.5mm [2.46in.]
LED Type	SMD2835
LED Qty	128LED/M [39LED/ft.]
Voltage	24VDC
Power	6W/M [1.83W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	980lm/M [300lm/ft.]
Light Efficiency @4000K&CRI90	163lm/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus [Dry/Damp/Wet]

Configuration reference

TRU-SWB24V128LEDM-C

Dimension	L20000*W8*H1.75mm [L787*W0.31*H0.07in.]
Increment	62.5mm [2.46in.]
LED Type	SMD2835
LED Qty	128LED/M [39LED/ft.]
Voltage	24VDC
Power	3W/M [0.91W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	520lm/M [160lm/ft.]
Light Efficiency @4000K&CRI90	173m/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus [Dry/Damp/Wet]

Configuration reference

TRU-SWB24V128LEDM-D

Dimension	L14000*W8*H1.75mm [L551*W0.31*H0.07in.]
Increment	62.5mm [2.46in.]
LED Type	SMD2835
LED Qty	128LED/M [39LED/ft.]
Voltage	24VDC
Power	6W/M [1.83W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1050lm/M [320lm/ft.]
Light Efficiency @4000K&CRI90	175m/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus [Dry/Damp/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.