WHITE LIGHT STRIPS

High-Efficacy Ultra-Long 173lm/W 10M 24V 240LED/M LED strip

TRU-SWC24V240LEDM

High-Efficacy Ultra-Long 173lm/W 10M 24V 240LED/M LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SWC24V240LEDM
Category	LED strips
Product type	White light strips

Configuration reference

TRU-SWC24V240LEDM-A

Dimension	L10000*W10*H1.75mm [L394*W0.39*H0.07in.]
Increment	33.33mm [1.31in.]
LED Type	SMD2835
LED Qty	240LED/M [73LED/ft.]
Voltage	24VDC
Power	12.5W/M [3.8W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	2000lm/M [610lm/ft.]
Light Efficiency @4000K&CRI90	160m/W
Beam Angle	120°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SWC24V240LEDM-B

Dimension	L7000*W10*H1.75mm [L276*W0.39*H0.07in.]
Increment	33.33mm [1.31in.]
LED Type	SMD2835
LED Qty	240LED/M [73LED/ft.]
Voltage	24VDC
Power	20W/M [6.1W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	3200lm/M [975lm/ft.]
Light Efficiency @4000K&CRI90	160lm/W
Beam Angle	120°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SWC24V240LEDM-C

Dimension	L10000*W10*H1.75mm [L394*W0.39*H0.07in.]
Increment	33.33mm [1.31in.]
LED Type	SMD2835
LED Qty	240LED/M [73LED/ft.]
Voltage	24VDC
Power	12.5W/M [3.8W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	2100lm/M [660lm/ft.]
Light Efficiency @4000K&CRI90	173m/W
Beam Angle	120°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SWC24V240LEDM-D

Dimension	L7000*W10*H1.75mm [L276*W0.39*H0.07in.]
Increment	33.33mm [1.31in.]
LED Type	SMD2835
LED Qty	240LED/M [73LED/ft.]
Voltage	24VDC
Power	20W/M [6.1W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	3400lm/M [1036lm/ft.]
Light Efficiency @4000K&CRI90	173m/W
Beam Angle	120°
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.