FLEXIBLE WALL WASHERS

Dual-Bend · Plus

TRU-WFA24V

Dual-Bend · Plus. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFA24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFA24V-A

Style	Dual-Bend (White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1800lm/M [550lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	100lm/W
Brightness @CRI90&3000K	Not specified
Light Efficiency @CRI90&3000K	Not specified
Beam Angle	15°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-B

Style	Dual-Bend (White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1800lm/M [550lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	100lm/W
Brightness @CRI90&3000K	1530lm/M [470lm/ft.]
Light Efficiency @CRI90&3000K	85lm/W
Beam Angle	25° / 30° / 45° / 60°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-C

Style	Dual-Bend (White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1600lm/M [490lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	89lm/W
Brightness @CRI90&3000K	1370lm/M [420lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	76lm/W
Beam Angle	15°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-D

Style	Dual-Bend (White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1600lm/M [490lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	89lm/W
Brightness @CRI90&3000K	1370lm/M [420lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	76lm/W
Beam Angle	25° / 30° / 45° / 60°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-E

Style	Dual-Bend (DMX White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	500mm [19.7in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	17W/M [5.18W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1650lm/M [500lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	97lm/W
Brightness @CRI90&3000K	1390lm/M [420lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	82lm/W
Beam Angle	15°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-F

Style	Dual-Bend (DMX White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	500mm [19.7in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	17W/M [5.18W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1650lm/M [500lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	97lm/W
Brightness @CRI90&3000K	1390lm/M [420lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	82lm/W
Beam Angle	25° / 30° / 45° / 60°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-G

Style	Dual-Bend (DMX White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	500mm [19.7in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	17W/M [5.18W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1500lm/M [460lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	88lm/W
Brightness @CRI90&3000K	1280lm/M [390lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	75lm/W
Beam Angle	15°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFA24V-H

Style	Dual-Bend (DMX White)
Dimension	W23xH23mm [W0.9xH0.9in.]
Increment	500mm [19.7in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	17W/M [5.18W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	1500lm/M [460lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	88lm/W
Brightness @CRI90&3000K	1280lm/M [390lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	75lm/W
Beam Angle	25° / 30° / 45° / 60°
IP&IK Rating	IP67 [Wet] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.