
FLEXIBLE WALL WASHERS

Dual-Bend · Plus

TRU-WFB24V

Dual-Bend · Plus. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFB24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFB24V-A

Style	Dual-Bend (White)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	2500lm/M [760lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	100lm/W
Brightness @CRI90&3000K	2130lm/M [650lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	85lm/W
Beam Angle	10°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-B

Style	Dual-Bend (White)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	2500lm/M [760lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	100lm/W
Brightness @CRI90&3000K	2130lm/M [650lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	85lm/W
Beam Angle	20° 25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-C

Style	Dual-Bend (White)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	2250lm/M [690lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	90lm/W
Brightness @CRI90&3000K	2130lm/M [650lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	77lm/W
Beam Angle	10°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-D

Style	Dual-Bend (White)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&3000K	2250lm/M [690lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	90lm/W
Brightness @CRI90&3000K	2130lm/M [650lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	77lm/W
Beam Angle	20° 25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-E

Style	Dual-Bend (RGBW)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	RGBW
Brightness @CRI80&3000K	1220lm/M [370lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	Not specified
Brightness @CRI90&3000K	1150lm/M [350lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	Not specified
Beam Angle	25° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-F

Style	Dual-Bend (RGBW)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	RGBW
Brightness @CRI80&3000K	1080lm/M [330lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	Not specified
Brightness @CRI90&3000K	1020lm/M [310lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	Not specified
Beam Angle	25° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-G

Style	Dual-Bend (DMX RGBW)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	DMX RGBW
Brightness @CRI80&3000K	950lm/M [290lm/ft.] (White Jacket)
Light Efficiency @CRI80&3000K	Not specified
Brightness @CRI90&3000K	890lm/M [270lm/ft.] (White Jacket)
Light Efficiency @CRI90&3000K	Not specified
Beam Angle	25° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFB24V-H

Style	Dual-Bend (DMX RGBW)
Dimension	W34xH25mm [W1.34xH0.98in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	DMX RGBW
Brightness @CRI80&3000K	860lm/M [260lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI80&3000K	Not specified
Brightness @CRI90&3000K	810lm/M [250lm/ft.] (Dark-Grey Jacket)
Light Efficiency @CRI90&3000K	Not specified
Beam Angle	25° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.