FLEXIBLE WALL WASHERS

DMX RGBW

TRU-WFC24V

DMX RGBW. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFC24V
Category	Wall washers
Product type	Flexible wall washers
Style	Top-Bend (DMX RGBW)
Dimension	W23xH11.5mm [W0.9xH0.45in.]
Increment	166.7mm [6.56in.] (6 pixel/M IC:UCS512C4)
LED Type	SMD 5050
LED Qty	36LED/M [11LED/ft.]
Voltage	24VDC
Power	23W/M [7W/ft.]
CCT / Wavelength	R:620-630mm G: 520530mm B:460-470mm W:2700~6500K
Brightness @CRI80&3000K	R: 200lm/M [60lm/ft.] G: 390lm/M [120lm/ft.] B: 100lm/M [30lm/ft.] W: 520lm/M [160lm/ft.]
Brightness @CRI90&3000K	R: 200lm/M [60lm/ft.] G: 390lm/M [120lm/ft.] B: 100lm/M [30lm/ft.] W: 440lm/M [130lm/ft.]
Beam Angle	40° 40°*45°

IP Rating	IP67 [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.