FLEXIBLE WALL WASHERS

# White High-Efficacy

**TRU-WFF24V**

White High-Efficacy. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



## Product specifications

| | |
|---|---|
| Truled part number | TRU-WFF24V |
| Category | Wall washers |
| Product type | Flexible wall washers |

## Configuration reference

### TRU-WFF24V-A

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2484lm/M [757lm/ft.] |
| Light Efficiency @CRI80&4000K | 138lm/W |
| Brightness @CRI90&4000K | 2106lm/M [642lm/ft.] |
| Light Efficiency @CRI90&4000K | 117lm/W |
| Beam Angle | 20° |
| IP Rating | IP67 [Wet] |

## Configuration reference

### TRU-WFF24V-B

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2448lm/M [746lm/ft.] |
| Light Efficiency @CRI80&4000K | 136lm/W |
| Brightness @CRI90&4000K | 2088lm/M [637lm/ft.] |
| Light Efficiency @CRI90&4000K | 116lm/W |
| Beam Angle | 30° |
| IP Rating | IP67 [Wet] |

## Configuration reference

### TRU-WFF24V-C

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2448lm/M [746lm/ft.] |
| Light Efficiency @CRI80&4000K | 136lm/W |
| Brightness @CRI90&4000K | 2088lm/M [637lm/ft.] |
| Light Efficiency @CRI90&4000K | 116lm/W |
| Beam Angle | 40° |
| IP Rating | IP67 [Wet] |

## Configuration reference

### TRU-WFF24V-D

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2376lm/M [724lm/ft.] |
| Light Efficiency @CRI80&4000K | 132lm/W |
| Brightness @CRI90&4000K | 2106lm/M [642lm/ft.] |
| Light Efficiency @CRI90&4000K | 112lm/W |
| Beam Angle | 60° |
| IP Rating | IP67 [Wet] |

## Configuration reference

### TRU-WFF24V-E

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2448lm/M [746lm/ft.] |
| Light Efficiency @CRI80&4000K | 136lm/W |
| Brightness @CRI90&4000K | 2088lm/M [637lm/ft.] |
| Light Efficiency @CRI90&4000K | 116lm/W |
| Beam Angle | 25°*35° |
| IP Rating | IP67 [Wet] |

## Configuration reference

### TRU-WFF24V-F

| | |
|---|---|
| Style | Top-Bend (White High-Efficacy) |
| Dimension | W23xH13.5mm [W0.9xH0.53in.] |
| Increment | 166.7mm [6.56in.] |
| LED Type | SMD 3030 |
| LED Qty | 42LED/M [12LED/ft.] |
| Voltage | 24VDC |
| Power | 18W/M [5.49W/ft.] |
| CCT / Wavelength | 2700K/3000K/ 4000K/6500K |
| Brightness @CRI80&4000K | 2340lm/M [713lm/ft.] |
| Light Efficiency @CRI80&4000K | 130lm/W |
| Brightness @CRI90&4000K | 1998lm/M [609lm/ft.] |
| Light Efficiency @CRI90&4000K | 111lm/W |
| Beam Angle | 15°*60° |
| IP Rating | IP67 [Wet] |

## Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.