FLEXIBLE WALL WASHERS

White Short-Cutting

TRU-WFG24V

White Short-Cutting. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFG24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFG24V-A

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1800lm/M [549lm/ft.]
Light Efficiency @CRI80&4000K	100lm/W
Brightness @CRI90&4000K	2106lm/M [642lm/ft.]
Light Efficiency @CRI90&4000K	85lm/W
Beam Angle	20°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFG24V-B

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1782lm/M [543lm/ft.]
Light Efficiency @CRI80&4000K	99lm/W
Brightness @CRI90&4000K	2088lm/M [637lm/ft.]
Light Efficiency @CRI90&4000K	84lm/W
Beam Angle	30°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFG24V-C

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1782lm/M [543lm/ft.]
Light Efficiency @CRI80&4000K	99lm/W
Brightness @CRI90&4000K	2088lm/M [637lm/ft.]
Light Efficiency @CRI90&4000K	84lm/W
Beam Angle	40°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFG24V-D

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1710lm/M [521lm/ft.]
Light Efficiency @CRI80&4000K	95lm/W
Brightness @CRI90&4000K	2106lm/M [642lm/ft.]
Light Efficiency @CRI90&4000K	81lm/W
Beam Angle	60°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFG24V-E

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1764lm/M [538lm/ft.]
Light Efficiency @CRI80&4000K	98lm/W
Brightness @CRI90&4000K	2088lm/M [637lm/ft.]
Light Efficiency @CRI90&4000K	83lm/W
Beam Angle	25°*35°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFG24V-F

Style	Top-Bend (White Short-Cutting)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	33.3mm [1.31in.]
LED Type	SMD 3030
LED Qty	30LED/M [9LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1692lm/M [516lm/ft.]
Light Efficiency @CRI80&4000K	94lm/W
Brightness @CRI90&4000K	1998lm/M [609lm/ft.]
Light Efficiency @CRI90&4000K	80lm/W
Beam Angle	15°*60°
IP Rating	IP67 [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.