FLEXIBLE WALL WASHERS

SPI White High-Efficacy

TRU-WFH24V

SPI White High-Efficacy. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFH24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFH24V-A

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2300lm/M [701lm/ft.]
Light Efficiency @CRI80&4000K	124lm/W
Brightness @CRI90&4000K	1940lm/M [591lm/f.]
Light Efficiency @CRI90&4000K	105lm/W
Beam Angle	20°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFH24V-B

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2280lm/M [695lm/ft.]
Light Efficiency @CRI80&4000K	123lm/W
Brightness @CRI90&4000K	1940lm/M [591lm/ft.]
Light Efficiency @CRI90&4000K	105lm/W
Beam Angle	30°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFH24V-C

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2240lm/M [683lm/ft.]
Light Efficiency @CRI80&4000K	121lm/W
Brightness @CRI90&4000K	1910lm/M [582lm/ft.]
Light Efficiency @CRI90&4000K	103lm/W
Beam Angle	40°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFH24V-D

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2200lm/M [671lm/ft.]
Light Efficiency @CRI80&4000K	119lm/W
Brightness @CRI90&4000K	1870lm/M [570lm/ft.]
Light Efficiency @CRI90&4000K	101lm/W
Beam Angle	60°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFH24V-E

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2240lm/M [683lm/ft.]
Light Efficiency @CRI80&4000K	121lm/W
Brightness @CRI90&4000K	1910lm/M [582lm/ft.]
Light Efficiency @CRI90&4000K	103lm/W
Beam Angle	25*35°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFH24V-F

Style	Top-Bend (SPI White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.] (6 pixel/M 3 points/pixel IC: UCS2093B)
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18.5W/M [5.64W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2150lm/M [655lm/ft.]
Light Efficiency @CRI80&4000K	116lm/W
Brightness @CRI90&4000K	1830lm/M [558lm/ft.]
Light Efficiency @CRI90&4000K	99lm/W
Beam Angle	15°*60°
IP Rating	IP67 [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.