FLEXIBLE WALL WASHERS

Flexible wall washers

TRU-WFI24V

Flexible wall washers. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFI24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFI24V-A

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2070lm/M [631lm/ft.]
Light Efficiency @CRI80&4000K	115lm/W
Brightness @CRI90&4000K	1760lm/M [537lm/ft.]
Light Efficiency @CRI90&4000K	98lm/W
Beam Angle	20°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFI24V-B

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2050lm/M [625lm/ft.]
Light Efficiency @CRI80&4000K	114lm/W
Brightness @CRI90&4000K	1750lm/M [534lm/ft.]
Light Efficiency @CRI90&4000K	97lm/W
Beam Angle	30°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFI24V-C

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2070lm/M [631lm/ft.]
Light Efficiency @CRI80&4000K	115lm/W
Brightness @CRI90&4000K	1760lm/M [537lm/ft.]
Light Efficiency @CRI90&4000K	98lm/W
Beam Angle	40°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFI24V-D

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2000lm/M [610lm/ft.]
Light Efficiency @CRI80&4000K	111lm/W
Brightness @CRI90&4000K	1690lm/M [515lm/ft.]
Light Efficiency @CRI90&4000K	94lm/W
Beam Angle	60°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFI24V-E

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	2030lm/M [619lm/ft.]
Light Efficiency @CRI80&4000K	113lm/W
Brightness @CRI90&4000K	1730lm/M [527lm/ft.]
Light Efficiency @CRI90&4000K	96lm/W
Beam Angle	25°*35°
IP Rating	IP67 [Wet]

Configuration reference

TRU-WFI24V-F

Style	Top-Bend (DMX White High-Efficacy)
Dimension	W23xH13.5mm [W0.9xH0.53in.]
Increment	166.7mm [6.56in.]
LED Type	SMD 3030
LED Qty	42LED/M [12LED/ft.]
Voltage	24VDC
Power	18W/M [5.49W/ft.]
CCT / Wavelength	2700K/3000K/ 4000K/6500K
Brightness @CRI80&4000K	1930lm/M [588lm/ft.]
Light Efficiency @CRI80&4000K	107lm/W
Brightness @CRI90&4000K	1640lm/M [500lm/ft.]
Light Efficiency @CRI90&4000K	91lm/W
Beam Angle	15°*60°
IP Rating	IP67 [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.