FLEXIBLE WALL WASHERS

Dual-Bend · Compact

TRU-WFL24V

Dual-Bend · Compact. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-WFL24V
Category	Wall washers
Product type	Flexible wall washers

Configuration reference

TRU-WFL24V-A

Style	Dual-Bend (White)
Dimension	W30xH23mm [W1.18xH0.91in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&4000K	2625lm/M [800lm/ft.] (White Jacket)
Light Efficiency @CRI80&4000K	105lm/W
Brightness @CRI90&4000K	2250lm/M [686lm/ft.] (White Jacket)
Light Efficiency @CRI90&4000K	90lm/W
Beam Angle	10°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFL24V-B

Style	Dual-Bend (White)
Dimension	W30xH23mm [W1.18xH0.91in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	2700K (2600-2750K) 3000K (2850-3100K) 4000K (3850-4150K)
Brightness @CRI80&4000K	2625lm/M [800lm/ft.] (White Jacket)
Light Efficiency @CRI80&4000K	105lm/W
Brightness @CRI90&4000K	2250lm/M [686lm/ft.] (White Jacket)
Light Efficiency @CRI90&4000K	90lm/W
Beam Angle	20° 25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFL24V-C

Style	Dual-Bend (RGBW)
Dimension	W30xH23mm [W1.18xH0.91in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	R:620-630nm G:520-530nm B:460-470nm W: 2700-6500K
Brightness @CRI80&4000K	1150lm/M [351lm/ft.] (White Jacket)
Light Efficiency @CRI80&4000K	46lm/W
Brightness @CRI90&4000K	1084lm/M [330lm/ft.] (White Jacket)
Light Efficiency @CRI90&4000K	43lm/W
Beam Angle	25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFL24V-C

Style	Dual-Bend (RGBW)
Dimension	W30xH23mm [W1.18xH0.91in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	R:620-630nm G:520-530nm B:460-470nm W: 2700-6500K
Brightness @CRI80&4000K	1150lm/M [351lm/ft.] (White Jacket)
Light Efficiency @CRI80&4000K	46lm/W
Brightness @CRI90&4000K	1084lm/M [330lm/ft.] (White Jacket)
Light Efficiency @CRI90&4000K	43lm/W
Beam Angle	25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-WFL24V-D

Style	Dual-Bend (DMX RGBW)
Dimension	W30xH23mm [W1.18xH0.91in.]
Increment	250mm [9.84in.]
LED Type	Not specified
LED Qty	24LED/M [7LED/ft.]
Voltage	24VDC
Power	25W/M [7.62W/ft.]
CCT / Wavelength	R:620-630nm G:520-530nm B:460-470nm W: 2700-6500K
Brightness @CRI80&4000K	1088lm/M [332lm/ft.] (White Jacket)
Light Efficiency @CRI80&4000K	Not specified
Brightness @CRI90&4000K	1022lm/M [316lm/ft.] (White Jacket)
Light Efficiency @CRI90&4000K	Not specified
Beam Angle	25° 30° 40° 50° 25°*50° 30°(asymmetric 15°)* 45°
IP&IK Rating	IP67 [Wet] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.